



SCAN  
FOR  
MORE  
INFO



## CLICKLIFT™

### Rapid manhole cover frame raising system

ClickLift eliminates the time and resources required to dig out and reinstall manhole frames to suit the final adoptable road surface. This eliminates the possibility for damage to occur to manhole covers during construction, minimises disruption and removes the potential for residents claims for damage to their vehicles. ClickLift provides housing developers and contractors with huge savings in terms of time, money and hassle. Allowing whole estates to have their covers raised to the final surfacing level, in as little as a few hours.

ClickLift simply clicks into place in Wrekin Highway and Tristar D400 600 x 600mm and 675 x 675mm manhole frames, in both 100mm and 150mm frame depths. Once in place it forms a BS EN 124 Kitemarked assembly for a D400 load class. Available in incremental depth increases between 30 to 60mm, to suit most common road surface finish depths.

#### KEY ATTRIBUTES

- ✓ Simple installation process requiring minimal tools and can be installed by a single person
- ✓ Available in a range of raising heights, 30mm, 40mm, 50mm and 60mm
- ✓ Can only be installed in one way, preventing incorrect installation
- ✓ Compliant with BS EN 124 and BSI Kitemarked
- ✓ Manufactured from highly durable ductile iron
- ✓ Compatible with Wrekin Highway and Tristar manhole cover ranges in both 600 x 600mm and 675 x 675 mm sizes



*ClickLift shown in yellow for visual purposes*

# CLICKLIFT

STOCK CODE	OVERALL FRAME (A X B MM)	CLEAR OPENING (C X D MM)	RAISING HEIGHT (E MM)
CLICKLIFT6030	640 x 640	600 x 600	30
CLICKLIFT6040	640 x 640	600 x 600	40
CLICKLIFT6050	640 x 640	600 x 600	50
CLICKLIFT6060	640 x 640	600 x 600	60
CLICKLIFT6730	715 x 715	675 x 675	30
CLICKLIFT6740	715 x 715	675 x 675	40
CLICKLIFT6750	715 x 715	675 x 675	50
CLICKLIFT6760	715 x 715	675 x 675	60

## DIMENSIONS

